

**DE** Stand 04.2024 | Revision C

**Produktdatenblatt  
Technische Daten**

**FINETT VISION | Wandbekleidung**

Nutzschicht	100 % Polyamid solution dyed														
Rücken	Textilrücken (Vlies)														
GWP (EPD A1-A3)	8,26 kg CO <sub>2</sub> -Äq./m <sup>2</sup>														
Recyclinganteil prEN 17903	35 %														
DGNB Kriterium ENV 1.2	Qualitätsstufe 4 (QS 4)														
REACH Verordnung Nr. 1907/2006 Artikel 33	enthält keine Stoffe aus der SVHC-Liste, die nach Artikel 33 deklariert werden müssen														
Flächengewicht ISO 8543	1700 g/m <sup>2</sup>														
Nutzschichteinsatzgewicht	800 g/m <sup>2</sup>														
Flächengewicht der Nutzschicht EN 984	750 g/m <sup>2</sup>														
Gesamtdicke ISO 1765	7,0 mm														
Abmessungen	Rollenbreite 200 cm   Rollenlänge 25-35 lfm														
Lichtechtheit EN ISO 105-B02	7														
Brandverhalten EN 13501-1	E														
Wärmedurchlasswiderstand ISO 8302	0,09 m <sup>2</sup> K/W														
Schallabsorptionsgrad EN ISO 354	<table border="1"> <thead> <tr> <th>Freq. Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α<sub>s</sub></td> <td>0,01</td> <td>0,05</td> <td>0,10</td> <td>0,25</td> <td>0,50</td> <td>0,73</td> </tr> </tbody> </table>	Freq. Hz	125	250	500	1000	2000	4000	α <sub>s</sub>	0,01	0,05	0,10	0,25	0,50	0,73
Freq. Hz	125	250	500	1000	2000	4000									
α <sub>s</sub>	0,01	0,05	0,10	0,25	0,50	0,73									
Sonderfarben	> 1000 m <sup>2</sup>														

Fordern Sie unbedingt vor der Bestellung ein größeres Muster zur Beurteilung der Farbwirkung an.

Produktionsbedingte Farbunterschiede zwischen Muster und Fertigware sowie technische Veränderungen, die der Produktverbesserung dienen, behalten wir uns vor. Unsere Verlegeanleitung sowie unsere Reinigungs- und Pflegeanleitung sind zu beachten.

Traditionelle textile Wandbekleidungen aus Nadelvlies bestehen aus einer Mischung verschiedenfarbiger Grobfasern, die beim fertigen Produkt für die typische, melierte Optik sorgen. Das Sortiment von FINDEISEN umfasst aber auch zahlreiche Ton-in-Ton Mischungen in Grob- und Feinfaseroptik. So entstehen besonders elegante Oberflächenstrukturen mit teilweise filzähnlicher Optik und weicher Haptik.

FINDEISEN Nadelvlies wird mit größter Sorgfalt und nach neuestem Stand der Technik im badischen Ettlingen hergestellt. Geringfügige optische Unregelmäßigkeiten im Warenbild (z. B. durch Fremdfasern) sowie Farbabweichungen sind produktionsbedingt nicht immer zu vermeiden und stellen keinen Mangel\* dar.

\*Die Pflichten des Verarbeiters nach § 377 HGB bleiben hiervon unberührt.



**EN** date of issue 04.2024 | revision C

## Technical data sheet

## FINETT VISION | Wall covering


Wear layer	100 % polyamide solution dyed														
Backing	Textile backing (non-woven fabric)														
GWP (EPD A1-A3)	8,26 kg CO <sub>2</sub> -Eq./m <sup>2</sup>														
Recycled content prEN 17903	35 %														
DGNB criterion ENV 1.2	Quality Level 4 (QL 4)														
REACH regulation No. 1907/2006 article 33	does not contain any substances from the SVHC list which have to be declared according to article 33														
Total weight ISO 8543	1700 g/m <sup>2</sup>														
Fiber weight	800 g/m <sup>2</sup>														
Wear layer weight EN 984	750 g/m <sup>2</sup>														
Total thickness ISO 1765	7,0 mm														
Dimensions	Roll width 200 cm   Roll length 25-35 m														
Colour fastness to light EN ISO 105-B02	7														
Fire rating EN 13501-1	E														
Thermal resistance ISO 8302	0,09 m <sup>2</sup> K/W														
Sound absorption EN ISO 354	<table border="1"> <thead> <tr> <th>Freq. Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α<sub>s</sub></td> <td>0,01</td> <td>0,05</td> <td>0,10</td> <td>0,25</td> <td>0,50</td> <td>0,73</td> </tr> </tbody> </table>	Freq. Hz	125	250	500	1000	2000	4000	α <sub>s</sub>	0,01	0,05	0,10	0,25	0,50	0,73
Freq. Hz	125	250	500	1000	2000	4000									
α <sub>s</sub>	0,01	0,05	0,10	0,25	0,50	0,73									
Special colours	> 1000 m <sup>2</sup>														

We highly recommend to ask for a larger sample before placing your order. Subject to product improvements and usual colour deviations. Please also consult our installation and cleaning maintenance instructions.

Textile wall coverings made from needled nonwoven consist of a mixture of coloured coarse fibers, which give the finished product the typical mottled look. The FINDEISEN range also includes numerous tone-on-tone blends in coarse and fine fiber looks. This results in particularly elegant surface textures with a partially felt-like appearance and a soft feel.

FINDEISEN wall coverings are manufactured with utmost care and according to the latest state of the art in Ettlingen/Germany. Minor optical irregularities in the appearance of the product (for example non-matching fibers) as well as colour deviations can not always be avoided due to the production process and are not a defect\*.

\*The obligations of the processor according § 377 HGB remain unaffected.



Member of the

