

BRIEF INSTRUCTION

Installation of modules and removable rolls

FINETT **DIMENSION** | FINETT **SOLID** modular

Date of issue 02.2025 | revision J

PREPARATION

1. Tools

- Adhesive tackifier
- 50 kg pressure roller
- Floor layer blade (hook and trapezoid blade)
- Ruler
- Multi pressure roller
- Coarse-pored foam roller (e.g. Storch roller art. no. 170825 or UZIN foam roller coarse art. no. 61983)



2. Suitable tackifiers (use undiluted!)

- ARDEX AF 185
 - BOSTIK Fix A995 Vlies
 - EUROCOL Eurofix Tiles 542
 - KLEBMUL HF Super
 - KIESEL Okatmos ER 15
 - MAPEI Ultrabond Eco Tack TX+
 - MUREXIN WL 730
 - SCHÖNOX Multifix
 - STAUF CT fix
 - THOMSIT K 145
 - UZIN U 2500
 - WAKOL D 3330
 - WAKOL D 3110
 - weber.floor 4870
 - WULFF Fixiergel
- ~~THOMSIT T 425 / T 435~~
~~UZIN U 1000~~
~~WAKOL D 965~~
~~ähnliche Produkte~~



3. Check delivery

- Matching colour and batch number



4. A/C

- Tackifier and needled carpet modules
- At least 24 hours
- Floor temperature: min. 15 °C
- Air temperature: 18-22 °C (max. 26 °C)
- Air humidity: 40-65%

Any questions?

Hotline
Application technology

+49 7243 7100-501
anwendungstechnik@nadelvlies.de



◀◀ **Detailed Installation Instruction**

www.nadelvlies.de/va_module_e.pdf

Video ▶▶

www.nadelvlies.de/va_module_video_e



5. Application tackifier

- Apply tackifier with a coarse-pored foam roller (e.g. Storch roller Art. No. 170825 or UZIN foam roller coarse Art. No. 61983) over the entire surface.




6. Drying

- After approx. 1 hour: Structured surface (coarse „orange peel“)





7. Installation

- Always install the modules and rolls in the same direction
- Note the lines resp. arrows on the back
- The following installation methods are permissible for tiles (50 x 50 cm) laying methods:



Parallel laying 

Braced laying 

Diagonal-laying 

(See also detailed laying instructions at www.nadelvlies.de/va_module_e.pdf)

8. Wall closure

- Modules: Double cut with 1-2 mm spacing (expansion joint)
- Rolls: 1-2 mm spacing (expansion joint)



9. Rolling

- 50 kg pressure roller - crossing over the entire surface



10. Final cleaning

- Thorough cleaning with brush vacuum cleaner

