

## BRIEF INSTRUCTION

Installation of modules and removable rolls

FINETT **DIMENSION** | FINETT **SOLID** modular | FINETT **CONTRACT**

### PREPARATION

#### 1. Tools

- Adhesive tackifier
- 50 kg pressure roller
- Floor layer blade (hook and trapezoid blade)
- Ruler
- Multi pressure roller
- Coarse-pored foam roller (e.g. Storch roller art. no. 170825 or UZIN foam roller coarse art. no. 61983)



#### 2. Suitable tackifiers (use undiluted!)

- ARDEX AF 185
- BOSTIK Fix A995 Vlies
- EUROCOL Eurofix Tiles 542
- KLEBMUL HF Super
- KIESEL Okatmos ER 15
- MAPEI Ultrabond Eco Tack TX+
- MUREXIN WL 730
- SCHÖNOX Multifix
- STAUF CT fix
- THOMSIT K 145
- UZIN U 2500
- WAKOL D 3330
- WAKOL D 3110
- weber.floor 4870
- WULFF Fixiergel



- ~~• THOMSIT T 425 / T 435~~
- ~~• UZIN U 1000~~
- ~~• WAKOL D 965~~
- ~~• ähnliche Produkte~~

#### 3. Check delivery

- Matching colour and batch number



#### 4. A/C

- Tackifier and needled carpet modules
- At least 24 hours
- Floor temperature: min. 15 °C
- Air temperature: 18-22 °C (max. 26 °C)
- Air humidity: 40-65%

Any questions?

**Hotline**  
**Application technology**

**+49 7243 7100-501**  
**anwendungstechnik@nadelvlies.de**



◀◀ **Detailed Installation Instruction**

[www.nadelvlies.de/va\\_module\\_e.pdf](http://www.nadelvlies.de/va_module_e.pdf)

**Video** ▶▶

[www.nadelvlies.de/va\\_module\\_video\\_e](http://www.nadelvlies.de/va_module_video_e)



### 5. Application tackifier

- Apply tackifier with a coarse-pored foam roller (e.g. Storch roller Art. No. 170825 or UZIN foam roller coarse Art. No. 61983) over the entire surface.



### 6. Drying

- After approx. 1 hour: Structured surface (coarse „orange peel“)



### 7. Installation

- Always install the modules and rolls in the same direction
- Note the lines resp. arrows on the back
- The following installation methods are permissible for tiles (50 x 50 cm) laying methods:



(See also detailed laying instructions at [www.nadelvlies.de/va\\_module\\_e.pdf](http://www.nadelvlies.de/va_module_e.pdf))

### 8. Wall closure

- Modules: Double cut with 1-2 mm spacing (expansion joint)
- Rolls: 1-2 mm spacing (expansion joint)



### 9. Rolling

- 50 kg pressure roller - crossing over the entire surface



### 10. Final cleaning

- Thorough cleaning with brush vacuum cleaner

